

STAINLESS STEEL SUMP PUMPS

DS SERIES

The Myers DS Series Stainless Steel Sump Pumps are designed for basement sumps, but are also ideal for dewatering duties in a variety of applications. This versatile pump features stainless steel construction for extreme resistance to corrosive environments and will provide years of superior service.

APPLICATIONS

Basement sumps, dewatering, and utility.

FEATURES

- ◆ **Versatile Performer:** Ideal for dewatering in construction sites, ponds, pits, tanks and water extraction from foundations and flooded basements.
- ◆ **Stainless Steel Tough:** Stainless steel housing and volute case resist corrosion and withstand the harshest conditions.
- ◆ **Powerful Start Ups:** High-torque, permanent split capacitor (PSC) motor; no relays or starting switches to wear out.
- ◆ **Double Protected Motor:** Long-life carbon/ceramic seal and additional lip seal protect motor against water leakage.
- ◆ **Extended Service:** Fully lubricated bearings and shaft seal for longer service life.
- ◆ **Smooth Operation:** Impeller is designed for clog resistance and effectively handles solids up to 3/4" in diameter.

SPECIFICATIONS


- ◆ **Capacities:** Up to 45 GPM (170.3 LPM)
- ◆ **Shut-Off Head:** Up to 26' (98.4 m)
- ◆ **Operation:** On = 13.5" (342.9 mm); Off = 6.75" (171.5 mm)
- ◆ **Solids Handling:** 3/4" (19 mm)
- ◆ **Liquids Handling:** Drain water
- ◆ **Continuous Liquid Temp.:** DS50P1 = 131°F (55°C)
- ◆ **Motor/Electrical Data:** 1/3 HP, 2.7A; 1/2 HP, 4.8A; 3/4 HP, 6.4A; 115V; 60Hz, permanent split capacitor type, 3450 RPM
- ◆ **Fittings Included:** 1-1/4" NPT x 1-1/4" NPT 90° discharge elbow, 1-1/4" NPT x 1-1/2" adapter.
- ◆ **Acceptable pH Range:** 5-9
- ◆ **Shaft Seal:** Dual lip with ceramic shaft seal
- ◆ **Housing:** Stainless steel
- ◆ **Power Cord:** 15', SJTW, 18/3
- ◆ **Discharge NPT:** 1-1/4"
- ◆ **Min. Sump Diameter:** 14"


 Tested & Certified to UL778
 and CSA 108.
3 Year Warranty



STAINLESS STEEL SUMP PUMPS DS SERIES

PUMP PERFORMANCE



ORDERING INFORMATION

CATALOG NUMBER	HP	VOLTS	PHASE	AMPS	DISCHARGE NPT	SWITCH TYPE	CORD LENGTH	APPROX. WT. LBS
DS50P1	1/2	115	1	4.8	1-1/4"	Tethered Automatic*	15'	16

*Piggyback



293 Wright St
Delavan, WI 53115
Ph: 888.987.8677
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

©2023 Pentair. All Rights Reserved.

M9016SSE (08-01-23)