

# **FX11+CR SYSTEM**

### FOODSFRVICE WATER TREATMENT SYSTEM

FX11+CR: 160-50012 Replacement Cartridges: CTO-10 252-00210 CCM-20 252-20620



### **APPLICATIONS**

Steam & combi ovens

Coffee & tea

#### **FEATURES • BENEFITS**

- Reduces maintenance frequency and cost, and extends equipment life
- Gradient-density sediment filtration protects against dirt, rust and other debris down to 0.5-microns
- Catalytic-carbon filtration provides added protection against chloramines that may be present in water supplies
- High-capacity activated-carbon filtration makes water taste great and protects equipment against corrosive chlorine

- Improves equipment operating efficiency
- Sturdy, powder-coated mounting bracket and full-flow inlet shut-off valve simplify installation
- Built-in pressure gauge allows visual monitoring of when filters need to be changed
- Inlet shut-off and depressurization valves make filter replacement quick and simple
- Minimizes waste by only replacing drop-in cartridge and reusing filter sump

#### **INSTALLATION TIPS**

- Feed-water connection to system should be COLD only.
- Do not exceed system specifications for temperature and pressure.
- Allow 3" clearance below system for filter housing removal and cartridge replacement.
- Connect filtered water line to ice and steam production connections only. Do not use for condenser water.
- Detailed installation, operation and maintenance manual included with each system.

#### **OPERATION TIPS**

- Change cartridges on a regular six (6) month preventative maintenance program.
- Change cartridges when capacity is reached or when flow becomes too slow.
- Always flush the filter cartridge at time of installation and cartridge change.

#### **SIZING**


- Service Flow Rate: 3.0 gpm (11.4 lpm)
- Rated Capacity: 20,000 gals. (75,708 L)

## FX11+CR SYSTEM

## 160-50012

FX11+CR: 160-50012

Replacement Cartridges: CTO-10 252-00210 CCM-20 252-20620



#### **SPECIFICATIONS**

- Service Flow Rate
   Maximum 3.0 gpm (11.4 Lpm)
- Rated Capacity
   20,000 gals. (75,708 L)
- Pressure Requirements
   10 125 psi (0.7 8.6 bar), non-shock
- Temperature
   35 100°F (2 38°C)
- Overall Dimensions
   24.6" L x 11.3" W x 5.8" D
   62.4 cm x 28.7 cm x 14.7 cm

- Inlet Connection 1/2" FNPT
- Outlet Connection 1/2" FNPT
- Shipping Weight 14 lbs (8.1 kgs)
- Electrical Connection
   None required

#### **WARRANTY**

Everpure water treatment systems by Pentair (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Pentair will provide a copy of the warranty upon request.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Since the conditions under which our products may be used are beyond our control, we cannot accept any liability with respect to the improper installation, application and/or use of our products.



United States | 1040 Muirfield Drive | Hanover Park, IL 60133 | 800.942.1153 (US Only) 630.307.3000 Main | cseverpure@pentair.com | foodservice.pentair.com | Australia | 1-21 Monash Drive | Dandenong South, Vic 3175 | Australia | 011.1300 576 190 Tel | au.everpure@pentair.com

China | 21F Cloud 9 Plaza, NO 1118 | Shanghai, 200052 | China | 86.21.3211.4588 Tel | china.water@pentair.com

India | Boulevard, B-9/A, 7th Floor - Tower B Sector 62 | Noida - 201301 | 91.120.419.9444 Tel | indiacustomer@pentair.com

Europe | Pentair Water Belgium BVBA | Industriepark Wolfstee, Toekomstlaan 30, B-2200 Herentals | Belgium | +32.(0).14.283.504 Tel | sales@everpure-europe.com Japan | Japan Inc. | Hashimoto MN Bldg. 7F, | 3-25-1 Hashimoto, Midori-ku, Sagamihara-shi | Kanagawa 252-0143 | Japan | 81.(0)42.775.3011 Tel | info@everpure.co.jp Southeast Asia | 390 Havelock Road, | #04-01 King's Centre | Singapore 169662 | 65.6768.5800 Tel | cseverpure@pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners
Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.