

### **SUBMITTAL**

# AURORA® 1070 DRY ROTOR SERIES AP9/APB9 CIRCULATORS

Job:	Representative:			
	Ordered by:	Date:		
Engineer:	Submitted by:	Date:		
Contractor:	Approved by:	Date:		

QUANTITY	TAG NO.	PART NUMBER	FLOW (USgpm)	HEAD (FEET)	VOLTAGE	PHASE	COMMENTS

#### **TECHNICAL DATA**

Flow Range: 0 to 38.0 USgpm (0 to 2.4 L/s)
Head Range: 0 to 42.4 feet (0 to 12.9 m)
Max/Min Fluid temp: 230°F/40°F (110°C/4°C)
Max. Working Pressure: 150 psi (1034 kPa)

#### **MATERIALS OF CONSTRUCTION**

Pump Body: Cast iron (closed systems)

Bronze (lead free for open systems)

Face Plate: Stainless steel
Impeller: 30% Glass-filled Noryl®

Volute Gasket: EPDM

**Bearings:** Permanently lubricated stainless steel **Seal:** Silicon carbide enviroseal c/w Viton® elastomer

#### **PART NUMBER**

	120V	240V
AP9	6365480642	6365481642
APB9	6365480644	6365481644

#### **APB9/APB9 ACCESSORIES**

- 3/4" Flange kits
- Timer
- 1" Flange kits
- Aquastat
- 1-1/4" Flange kits
- Spool pieces
- 1-1/2" Flange kits


#### **MOTOR DATA**

Voltage	120V	208V	240V
Full Load Amp Draw	2.0A	1.0A	1.0A


Nominal Power: 1/6 hp (125w) Frequency: 60 Hz

Motor Type: Two pole, Single phase Speed: 3250 rpm

#### MOUNTING ORIENTATION For indoor use only



#### **PERFORMANCE CURVE**



Performance curves are for reference only.

## **AURORA**° 1070 DRY ROTOR SERIES AP9/APB9 CIRCULATORS

DIMENSIONS INCHES (mm)							SHIP WEIGHT		
MODEL	BODY	Α	В	С	D	E	F	CONNECTION TYPE & SIZE	lbs (kgs)
AP9	Cast iron	7.10	6.40	5.50	3.80	3.20	4.20	1.25" diameter 2-bolt flanges	12.25 (5.55)
		(180)	(164)	(140)	(97)	(81)	(107)		
APB9	Bronze	7.10	6.40	5.50	3.80	3.20	4.20	1.25" diameter 2-bolt flanges	13.55 (6.15)
		(180)	(164)	(140)	(97)	(81)	(107)		

