

SUBMERSIBLE SOLIDS HANDLING PUMPS

4HC(X), 6MC(X) SERIES

RPM	1750			
MOTOR TYPE	PREMIUM EFFICIENT, IEC 60034 -30 LEVEL IE3 *			
MOTOR DESIGN NEMA TYPE	A or B (3Ø)			
GENERAL INSULATION CLASS	H			
STATOR WINDING CLASS	H			
MAXIMUM STATOR TEMPERATURE RATING	356°F (180°)			
MOTOR PROTECTION	3 PHASE, BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 130°C AND AUTOMATICALLY RESET @ 82°C DIFFERENTIAL			
ELECTRICAL RATINGS	HEAT SENSOR	24VDC 5 AMPS	115VAC 5AMPS	230VAC 5AMPS
	SEAL FAIL	300VAC 5mA		
VOLTAGE TOLERANCE	±10%			

*208V versions and 20/23HP models will not conform to IE3 standards.

HP	VOLTAGE	PHASE	NEC CODE	SF	FULL LOAD AMPS	SF AMPS	LOCKED ROTOR AMPS	RUN KW	START KVA	RUN KVA	MTR. EFFICIENCY @100% FL	PWR. FACT. @SF	PWR. FACT. @100% FL	PWR. FACT. @75% FL	PWR. FACT. @50% FL
15	208	3	K	1.15	46.4	55.3	353.0	13.7	127.0	16.7	92.4	83.5	81.8	77.3	68.6
	230				42.0	50.0	320.0	13.7	127.3	16.7	92.4	83.5	81.8	77.3	68.6
	460				21.0	25.0	160.0	13.7	127.3	16.7	92.4	83.5	81.8	77.3	68.6
	575				J	16.8	20.0	120.0	13.7	119.4	16.7	92.4	83.5	81.8	77.3
20	208	3	H	1.15	58.6	64.6	353.0	18.0	127.0	21.1	93.0	85.8	84.9	81.8	75.0
	230				53.0	58.4	320.0	18.0	127.3	21.1	93.0	85.8	84.9	81.8	75.0
	460				26.5	29.2	160.0	18.0	127.3	21.1	93.0	85.8	84.9	81.8	75.0
	575				G	21.2	23.4	120.0	18.0	119.4	21.1	93.0	85.8	84.9	81.8
23	230	3	F	1.0	58.4	58.4	320.0	20.1	127.3	23.2	93.0	-	85.8	83.5	77.6
	460				29.2	29.2	160.0	20.1	127.3	23.2	93.0	-	85.8	83.5	77.6
	575				23.4	23.4	120.0	20.1	119.4	23.3	93.0	-	85.8	83.5	77.6

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com/hydromatic