

SUBMERSIBLE SOLIDS HANDLING PUMPS

S12L(X)P

PHYSICAL DATA

DISCHARGE SIZE		12"
IMPELLER TYPE		BALANCED, ENCLOSED, 2 VANE
CABLE LENGTH	Standard:	35'
	Optional:	50', 75, 100'

LIQUID HANDLING

SOLIDS SIZE		6"
MAXIMUM LIQUID TEMP.		140°F
ACCEPTABLE PH RANGE		6-9
SPECIFIC GRAVITY		0.9-1.1
VISCOSITY		28-35 SSU

TEMPERATURE

MAXIMUM STATOR		311°F
OIL FLASH POINT		390°F
HEAT SENSOR	Open:	311°F MAX./293°F MIN.
	Closed:	243°F MAX./192°F MIN.

TECHNICAL DATA

POWER CORD TYPE		SOOW, W, GGC			
SENSOR CORD TYPE		SOOW			
MATERIALS OF CONSTRUCTION	MOTOR HOUSING	CAST IRON	ASTM	A-48	CLASS 30
	CASING	CAST IRON	ASTM	A-48	CLASS 30
	IMPELLER	DUCTILE IRON	ASTM	A-536	
	CASING WEAR RING	BRONZE	ASTM	B-584-836	ALLOY 115
	MOTOR SHAFT	416 STAINLESS STEEL			
	HARDWARE	300 SERIES STAINLESS STEEL			
	"O" RINGS	NITRILE			
MECHANICAL SEALS	Standard:	UPPER - CARBON/SILICON CARBIDE/FLUROCARBON, TYPE 2100, LOWER - SILICON CARBIDE/CARBON/FLUROCARBON, TYPE 2			
	Optional:	UPPER SILICON CARBIDE/SILICON CARBIDE/FLUROCARBON, TYPE 2100			
	Optional:	LOWER TUNGSTEN CARBIDE/TUNGSTEN CARBIDE/FLUROCARBON, TYPE 2			
	Optional:	LOWER SILICON CARBIDE/SILICON CARBIDE/FLUROCARBON, TYPE 2			
UPPER BEARING		(RADIAL) SINGLE ROW-BALL			
LOWER BEARING		(THRUST) DOUBLE ROW, ANGULAR CONTACT-BALL			

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com