

SUBMERSIBLE SOLIDS HANDING PUMPS

S8L(X)P

RPM	1150		
MOTOR TYPE	PREMIUM EFFICIENT, IEC 60034-30 LEVEL IE3		
MOTOR DESIGN NEMA TYPE	A (3 ϕ)		
GENERAL INSULATION CLASS	H		
STATOR WINDING CLASS	H		
MAXIMUM STATOR TEMPERATURE	356°F (180°)		
MOTOR PROTECTION	BI-METALLIC, TEMPERATURE SENSITIVE DISC, SIZED TO OPEN AT 150°C AND AUTOMATICALLY RESET @ 117-89°C DIFFERENTIAL, THREE IN THREE PHASE		
ELECTRICAL RATINGS	HEAT SENSOR	24 VDC 5 AMPS	115 VAC 5 AMPS
	SEAL FAILURE	300 VAC 5 Ma	
VOLTAGE TOLERANCE	±10%		

HP	VOLTAGE	PHASE	NEMA CODE	SF	NAME PLATE AMPS	SF AMPS	LOCK ROTOR AMPS	RUN KW	START KVA	RUN KVA	NEMA REQ. PREMIUM EFFICIENCY AT FL	MOTOR EFF. AT SF*	MOTOR EFF. AT FL*	MOTOR EFF. AT 75% FL*	MOTOR EFF. AT 50% FL*	POWER FACTOR AT SF	POWER FACTOR AT FL	POWER FACTOR AT 75% FL	POWER FACTOR AT 50% FL
40	460	3	K	1.3	54	63	420	36.5	349.2	43.0	94.1	93	94.1	93	91.5	0.865	0.85	0.84	0.83
	575				43.2	50.4	351												
50	460	3	H	1.3	64.0	79.0	420	44.1	349.2	50.9	94.1	93.1	94.1	93	91.6	0.865	0.865	0.85	0.84
	575				51.2	63.2	351												
60	460	3	J	1.3	78.0	95.0	503	54.0	426.7	62.1	94.5	93.2	94.5	93.2	91.8	0.875	0.87	0.86	0.85
	575				62.4	76.0	429												

*Motor efficiency does not include seal and oil losses per IEC60034-30 5.1.3. Full load amps and service factor amps do include these losses.

1101 Myers Parkway
Ashland, OH 44805
Ph: 855.274.8947
Fx: 800.426.9446

490 Pinebush Rd., Unit 4
Cambridge, Ontario N1T 0A5, Canada
Ph: 800.363.7867
Fx: 888.606.5484

pentair.com

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.