

PRESSURE TANKS





MODEL LT2 MODEL LT5

- Tough, appliance-like finish for extended life
- Heavy gauge steel construction for maximum durability
- Air/water separator for easy maintenance
- Factory pre-charged at 20 PSI
- 3/4" NPT male plumbing connection
- Certified to ANSI/NSF 61



PERFORMANCE

Model	Style	Warranty	Rated Size in Gallons	Actual Capacity in Gallons	Plumbing Connection	Tank Height
LT2	In-Line	5-year	6	2	3/4"	12.6"
LT5	In-Line	5-year	15	5	3/4"	16.2"

Pressure Switch	Type of	Usable Water* per "Rated" Tank Size in Gallons			
Setting	Tank	6	15		
20-40	Standard	0.9	2.3		
	Precharged	0.7	2.2		
30-50	Standard	0.6	1.5		
	Precharged	0.6	1.8		
40-60	Standard	0.4	1.1		
	Precharged	N/A	1.8		

^{*}Usable water between pump cycles. The larger the usable water the less frequently the pump will cycle (turn off and on) thereby increasing pump life. Purchase the largest tank size possible for your application to maximize the life expectancy of your total water system.

ORDERING INFORMATION

Model	UPC	Carton (L x W x H)	Cube	Pallet Qty.	Weight
LT2	0 17561 70012 6	8.38" x 8.50" x 12.75"	.526	70	6.35 lbs.
LT5	0 17561 70013 3	10.75" x 11" x 18"	1.231	70	11.25 lbs.

www.simerpump.com • 1-800-468-7867